



EO MINI PRO 3

Impossibly small.
Impressively smart.



EO MINI PRO 3

DESIGNED AND MANUFACTURED
IN THE UNITED KINGDOM.

FEATURES

- + Connection type: Universal Type 2 socket, Type 1 and Type 2 tethered cable (5m)
- + Power ratings: Single-phase up to 7.2kW (Type 1 & Type 2), three-phase up to 22kW (Type 2 only)
- + Solar charging: Charge your car with our solar matching or net-zero technologies (optional extra, using an additional CT clamp)¹
- + Connectivity: Wi-Fi, Cat 5 Ethernet, Bluetooth as standard, 4G cellular¹ as optional extra
- + Integrated RFID reader & EO branded RFID tags available (optional)¹

INSTALLATION

- + Simple electrical installation
- + Integral 6mA DC leakage detection, no Type B RCD required
- + Adjustable maximum charging current for lower rated supplies
- + TN & IT grid connections



INTELLIGENCE

- + OCPP 1.6J: Back-office agnostic, ready for open OCPP integration and additional security extensions
- + Built-in power balancing with OCPP or locally via CT clamp
- + ISO15118 ready for vehicle-to-grid (V2G) and plug & charge functionality¹
- + EO Hub 2: Connect an unlimited number of chargers to the EO Hub 2¹ for small commercial installations and additional load management
- + Smartphone app controlled: Energy usage monitoring and charging sessions management using our iOS and Android smartphone app

¹Feature not available with V1 product. V2 coming soon.

MODEL ORDER CODE	EM301-DCL	EM303-DCL
DESCRIPTION	EO Mini Pro 3 Single-phase charger - locking socket	EO Mini Pro 3 Three-phase charger - locking socket

ELECTRICAL DATA		
RATED POWER	Up to 7.2kW	Up to 22kW
CHARGING CURRENT	6A to 32A (variable)	6A to 32A (variable)
RATED CURRENT	Up to 32A max	Up to 32A max
NOMINAL SUPPLY	230VAC 50Hz	400VAC 50Hz
SUPPLY CONNECTIONS	L1, N, PE 2.5 - 10mm ²	
OVER CURRENT CONNECTION	40A supply	40A supply
EARTH LEAKAGE PROTECTION	A dedicated 30mA Type A RCD must be used on the supply circuit. Integral 6mA DC leakage detection - no Type B RCD required	
STANDBY POWER CONSUMPTION	<3W	
STATUS INDICATION	3 colour LED indicator (green, blue, red)	
CHARGING MODE	Mode 3 (IEC 61851-1 compliant communication protocol)	
SOCKET	IEC 62196 Type 2, IP54 hinged lid, locking pin	
SUPPLY CABLE ENTRY	Ø25mm modifiable cable entry (Ø10mm - Ø22mm PVC stepped grommet included)	

MECHANICAL DATA	
DIMENSIONS (H x W x D)	215mm x 140mm x 100mm
UNIT WEIGHT	<2kg (socketed), <5kg (tethered)
MOUNTING LOCATION	Wall or post mounted, indoor or outdoor (post mounting requires additional backplate, available as an extra)
AMBIENT TEMPERATURE	-30°C to +55°C
INTERNAL ELECTRONICS TEMPERATURE	-25°C to +50°C
OPERATING HUMIDITY	5 to 95% relative humidity
ENCLOSURE	PC UV stabilized (UL94 V-0 fire rated)
PROTECTION	IP66 / IP54
IMPACT RATING	IK08
STANDARD FINISH	Black (RAL9005), removable fascia
OPTIONAL FINISH	Co-branding options available, subject to MOQs

COMMUNICATIONS
U.FI external antennae ports for Wi-Fi, BTE & 4G cellular ¹ 10/100Mbit RJ45 Ethernet ¹

COMPLIANCE
BSI Kitemark (pending) CE + UKCA Marked, EMC Directive 2014/30/EU, IEC 61851-1, IEC 61851-22, IEC 62196-2 EN 301-489 RFID - ISO/IEC 14443 (MIFARE). ETSI EN 303 645 cybersecurity

OPTIONS
4G cellular (GPRS, NB-IoT/2G) ¹ RFID card reader Tethered Type 1/Type 2 cable (5m) Additional backplate for post mounting T2S socket Cloud-based static load management using OCPP via smart charging profiles Local automatic load management (using an additional CT clamp) EO Hub 2 for local automatic load management of multiple charging stations ¹ ISO15118 for vehicle-to-grid (V2G) and plug & charge functionality ¹ Solar charging (using an additional CT clamp) ¹ Co-branding options available, subject to MOQs

¹Feature not available with V1 product. V2 coming soon.